

Inspection Pit Dimensions Equipment or Rig Type Dando Terrier					Hand Vane: Raw Data							
					Type	Geonor	Pilcon	Impact				
					16		19		19			
					Size (mm)	20		33		33		
Window Sampling: Tube Driving Data					25	Tick one box						
Tube dia (mm)	Depth		Recovery (m)	Time (min:sec)	Casing depth (windowless)	Depth	Peak			Remoulded		
	From	To					1	2	3	1	2	3
102	GL	1.00	0.80									
87	1.00	1.30	0.20									
					Pocket Penetrometer: Raw Data							
					Depth	1	2	3	4	5	6	
All depths are m below ground level					Use GDMS data entry to input raw data to HoleBASE							
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
no sample		GL	0.50	Soft dark brown slightly sandy slightly gravelly CLAY. Gravel is subangular fine to medium of siltstone. TOPSOIL.								
		0.50	1.30	Grey slightly clayey subrounded to rounded fine to coarse GRAVEL of siltstone and mudstone with low cobble content of subrounded to rounded siltstone and mudstone. RIVER TERRACE DEPOSITS.								
						Backfill Details (if no installation)						
Key to soil samples:			B = bulk	D = tub	L = liner	ES = environmental soil						
Groundwater Strike	If Yes			Project			Project No					
	No	Depth of strike	After 20 mins	Depth sealed	Nantgaredig							
Remarks				Operator	APEX	Date	Hole No.					
Liners sampled to bulk bags				Logger	PL	Date						
						23/03/2020	WS02					
						23/03/2020						