

<b>Inspection Pit Dimensions</b>					<b>Hand Vane: Raw Data</b>							
					Type	Geonor	Pilcon	Impact				
<b>Equipment or Rig Type</b> Dando Terrier					16		19		19			
					Size (mm)	20		33		33		
<b>Window Sampling: Tube Driving Data</b>					25	Tick one box						
Tube dia (mm)	Depth		Recovery (m)	Time (min:sec)	Casing depth (windowless)	Depth	Peak			Remoulded		
	From	To					1	2	3	1	2	3
102	GL	0.90	0.90									
All depths are m below ground level					Use GDMS data entry to input raw data to HoleBASE							
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
0.30-0.60	B	GL	0.60	Soft dark brown slightly sandy slightly gravelly CLAY. Gravel is subangular fine to medium of siltstone. TOPSOIL.								
		0.60	0.90	Grey clayey subrounded to rounded fine to coarse GRAVEL of siltstone and mudstone with low cobble content of subrounded to rounded siltstone and mudstone. RIVER TERRACE DEPOSITS.								
							<b>Backfill Details</b> (if no installation)					
Key to soil samples:			B = bulk	D = tub	L = liner	ES = environmental soil						
Groundwater Strike		If Yes			Project			Project No				
No		Depth of strike	After 20 mins	Depth sealed	Nantgaredig			2031				
Remarks					Operator		Date		Hole No.			
Liners sampled to bulk bags					APEX		23/03/2020					
					Logger		PL		Date			
							23/03/2020		WS05			