# Window Sampling Hole Journal

**Inspection Pit Dimensions**

**Equipment or Rig Type** Dando Terrier

**Hand Vane: Raw Data**

| Type | Geonor | Pilcon | Impact |
|---|---|---|---|
| Size (mm) | 16 ☐ | 19 ☐ | 19 ☐ |
| | 20 ☐ | 33 ☐ | 33 ☐ |
| | 25 ☐ | Tick one box | |

**Window Sampling: Tube Driving Data**

| Tube dia (mm) | Depth From | Depth To | Recovery (m) | Time (min:sec) | Casing depth (windowless) |
|---|---|---|---|---|---|
| 102 | GL | 0.90 | 0.90 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| Depth | Peak 1 | Peak 2 | Peak 3 | Remoulded 1 | Remoulded 2 | Remoulded 3 |
|---|---|---|---|---|---|---|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

**Pocket Penetrometer: Raw Data**

| Depth | 1 | 2 | 3 | 4 | 5 | 6 |
|---|---|---|---|---|---|---|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

All depths are m below ground level

Use GDMS data entry to input raw data to HoleBASE

| Samples Type | No. | Depth | Strata Depth | Description |
|---|---|---|---|---|
| no sample | | GL | 0.40 | Soft dark brown slightly sandy slightly gravelly CLAY. Gravel is subangular fine to medium of siltstone. TOPSOIL |
| | | 0.40 | 0.60 | Grey and brown slightly gravelly clayey fine to medium SAND. GRAVEL is subangular to subrounded fine to coarse of siltstone and mudstone with low cobble content of subrounded to rounded siltstone and mudstone. RIVER TERRACE DEPOSITS. |
| | | 0.60 | 0.90 | Grey slightly clayey subrounded to rounded fine to coarse GRAVEL of siltstone and mudstone with low cobble content of subrounded to rounded siltstone and mudstone. RIVER TERRACE DEPOSITS. |

**Installation Details**

**Backfill Details** (if no installation)

Key to soil samples: B = bulk D = tub L = liner ES = environmental soil

**Groundwater Strike**

| If Yes | | |
|---|---|---|
| Depth of strike | After 20 mins | Depth sealed |
| No | | |

Project: Nantgaredig

**Project No** 2031

**Remarks** Liners sampled to bulk bags

Installation: GL - 0.30m 50mm plain pipe

0.30 - 0.90m 50mm slotted pipe

Operator APEX Date 23/03/2020

Logger PL Date 23/03/2020

**Hole No.** WS06